

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Mold Brite
Product code : MB-200-5, MB-200-55

1.2. Recommended use and restrictions on use

Recommended use : Mold cleaner
Restrictions on use : None

1.3. Supplier

Nanoplas Inc.
2950 Prairie Street South West
Suite 900
Grandville, MI, 49418
T (616)-452-3707
info@nanomoldcoating.com

1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call INFOTRAC 24hr/day 7days/week
(collect calls accepted)
Within USA, Mexico and Canada: 800-535-5053 ID# 102222
Outside USA, Mexico and Canada: 1-352-323-3500 ID# 102222

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Eye irritation Category 2A	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) :
H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing mist, spray, vapors.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P331 - Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a poison center or doctor if you feel unwell.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P370+P378 - In case of fire: Use dry extinguishing powder, carbon dioxide (CO₂), alcohol resistant foam to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Heptane, branched, cyclic and linear	CAS-No.: 426260-76-6	≥ 80
Propan-2-ol, isopropyl alcohol, isopropanol	CAS-No.: 67-63-0	10 – 20
heptane, n-heptane	CAS-No.: 142-82-5	1 – 5
Citrus Aurantium Dulcis (orange) oil	CAS-No.: 8008-57-9	< 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Move the affected person to fresh air. Get medical attention if symptoms occur.
First-aid measures after skin contact	: Take off contaminated clothing. Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: Aspiration hazard. May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.
Inhalation	: May cause drowsiness or dizziness. High concentration of vapors may induce: headache, nausea, dizziness. May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: Causes skin irritation.
Eyes	: Causes serious eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: No chronic health hazards are likely for this material.

4.3. Immediate medical attention and special treatment, if necessary

Aspiration hazard. If accidentally swallowed obtain immediate medical attention.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water fog. Alcohol-resistant foam. Carbon dioxide (CO ₂). Dry chemical. Cool down the containers exposed to heat with a water spray.
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.
Explosion hazard	: vapors may form explosive mixture with air.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Hydrocarbon. Carbon oxides (CO, CO ₂).

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ventilate area. Eliminate ignition sources. Wear suitable protective clothing. Avoid contact with eyes, skin and clothing.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: Remove all sources of ignition. No open flames, no sparks, and no smoking. Avoid breathing mist, spray, vapors. Avoid contact with skin and eyes. Keep unnecessary and unprotected personnel away from the spillage.
----------------------	--

Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dike and contain spill.
Methods for cleaning up : Ventilate area. No flames, no sparks. Eliminate all sources of ignition. Absorb with an inert material and place in an appropriate waste disposal container. Use personal protective equipment as required. Notify authorities if product enters sewers or public waters.
Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of contaminated materials refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure adequate ventilation. Use explosion-proof equipment. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use only non-sparking tools. Flammable vapors may accumulate in the container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Keep container closed when not in use. Handle in accordance with good industrial hygiene and safety procedures.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Incompatible materials : Strong oxidizers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024

Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

USA - ACGIH - Biological Exposure Indices

Local name	2-Propanol
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Isopropyl alcohol
OSHA PEL (TWA)	980 mg/m ³
	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

heptane, n-heptane (142-82-5)

USA - ACGIH - Occupational Exposure Limits

Local name	Heptane, isomers (n-Heptane)
ACGIH OEL TWA	400 ppm
ACGIH OEL STEL	500 ppm
Remark (ACGIH)	TLV® Basis: CNS impair; URT irr
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Heptane (n-Heptane)
OSHA PEL (TWA)	2000 mg/m ³
	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure adequate ventilation. Use explosion-proof equipment.
Environmental exposure controls	: Do not allow product to spread into the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves

Eye protection:

Chemical goggles

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Thermal hazard protection:

Not applicable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear. Amber Liquid.
Color	: Amber
Odor	: Fragrance-specific odor
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -7 °C Based on data available for ingredients
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.7
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: < 20.5 mm ² /s
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: vapors may form flammable and explosive mixture with air.
Oxidizing properties	: Not oxidising.
Particle Characteristics	: Not applicable

9.2. Other information

VOC content : 99.55 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizers.

Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

LD50 oral rat	5840 mg/kg
LD50 dermal rabbit	16.4 ml/kg
LC50 Inhalation - Rat [ppm]	1666.66 ppm/1h

heptane, n-heptane (142-82-5)

LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 29300 mg/m³

Citrus Aurantium Dulcis (orange) oil (8008-57-9)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified. This product does not contain any component that is considered a carcinogen by IARC, ACGIH, OSHA or NTP.

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Heptane, branched, cyclic and linear (426260-76-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

heptane, n-heptane (142-82-5)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

heptane, n-heptane (142-82-5)

LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male

Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: < 20.5 mm²/s

Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

Viscosity, kinematic	2.58 mm ² /s
----------------------	-------------------------

heptane, n-heptane (142-82-5)

Viscosity, kinematic	0.641 mm ² /s at 20 C
----------------------	----------------------------------

Symptoms/effects	: Aspiration hazard. May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.
Inhalation	: May cause drowsiness or dizziness. High concentration of vapors may induce: headache, nausea, dizziness. May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: Causes skin irritation.
Eyes	: Causes serious eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: No chronic health hazards are likely for this material.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Very toxic to aquatic life with long lasting effects.
-------------------	---

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

LC50 - Fish [1]	10000 mg/l Pimephales promelas (Fathead minnow)
EC50 - Crustacea [1]	> 10000 mg/l
LC50 - Fish [2]	9640 mg/l Pimephales promelas (Fathead minnow)
NOEC chronic crustacea	3.37 mg/l

heptane, n-heptane (142-82-5)

EC50 - Crustacea [1]	3.9 mg/l
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Mold Brite

Persistence and degradability	No data available.
-------------------------------	--------------------

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Heptane, branched, cyclic and linear (426260-76-6)

Persistence and degradability	Inherently biodegradable.
-------------------------------	---------------------------

heptane, n-heptane (142-82-5)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Citrus Aurantium Dulcis (orange) oil (8008-57-9)

Persistence and degradability	No data available.
-------------------------------	--------------------

Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

12.3. Bioaccumulative potential

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

BCF - Fish [1]	3
Partition coefficient n-octanol/water (Log Kow)	0.05

12.4. Mobility in soil

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.5
--	-----

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
1993	1993	1993
14.2. Proper Shipping Name		
Flammable liquids, n.o.s. (Heptane, Isopropanol)	FLAMMABLE LIQUID, N.O.S. (Heptane, Isopropanol)	Flammable liquid, n.o.s. (Heptane, Isopropanol)
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

14.6. Special precautions for user

DOT

UN-No.(DOT)	: UN1993
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F). TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

IMDG

Special provision (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28, TP8
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: B

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A3
ERG code (IATA)	: 3H

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

SECTION 15: Regulatory information

15.1. US Federal regulations

Mold Brite

SARA Section 311/312 Hazard Classes

Refer to Section 2 for OSHA Hazard Classification.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Propan-2-ol, isopropyl alcohol, isopropanol(67-63-0)	U.S. - New Jersey - Right to Know Hazardous Substance List
heptane, n-heptane(142-82-5)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Revision date : 7/19/2024

Full text of H-phrases

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

NFPA health hazard


: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Mold Brite

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Hazard Rating	
Health	: 3 Serious Hazard
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

Indication of changes:
All chapters have been modified since the previous version. revised edition.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.