

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : MOLD GUARD GREEN
Product code : MG-50G-5, MG-50G-55

1.2. Recommended use and restrictions on use

Recommended use : Rust Preventative
Restrictions on use : None known

1.3. Supplier

Nanoplas Inc.
2950 Prairie Street South West
Suite 900
Grandville, MI, 49418
T (616)-452-3707
info@nanomoldcoating.com

1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call INFOTRAC 24hr/day 7days/week
(collect calls accepted)
Within USA, Mexico and Canada: 800-535-5053 ID# 102222
Outside USA, Mexico and Canada: 1-352-323-3500 ID# 102222

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :   

Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing mist, spray, vapors.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P331 - Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P363 - Wash contaminated clothing before reuse.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a poison center or doctor if you feel unwell.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, foam to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Heptane, branched, cyclic and linear	CAS-No.: 426260-76-6	75 - 85
Mineral Oil	CAS-No.: Proprietary	5 – 10
Barium Alkylnaphthalenesulfonate Mixture	CAS-No.: Proprietary	5 – 10
heptane, n-heptane	CAS-No.: 142-82-5	1 – 5
Xylene	CAS-No.: 1330-20-7	< 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Move the affected person to fresh air. Get medical attention if symptoms occur.
First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash skin with plenty of water. Get medical advice if skin irritation persists. Wash contaminated clothing before reuse.
First-aid measures after eye contact : Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists.

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

First-aid measures after ingestion : Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: Aspiration hazard. May be fatal if swallowed and enters airways. Causes skin irritation. May cause minor eye irritation. May cause drowsiness or dizziness.
Inhalation	: High concentration of vapors may induce: headache, nausea, dizziness. May cause minor irritation to the respiratory tract and to other mucous membranes. Intentional abuse may be harmful or fatal.
Skin	: May cause slight irritation to the skin. Causes skin irritation.
Eyes	: May cause minor eye irritation.
Ingestion	: Aspiration hazard. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: No chronic health hazards are likely for this material.

4.3. Immediate medical attention and special treatment, if necessary

Aspiration hazard. If accidentally swallowed obtain immediate medical attention.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry chemical, CO ₂ , or water spray or regular foam.
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor. Keep away from open flames, hot surfaces and sources of ignition. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Barium and compounds. Carbon oxides (CO, CO ₂). Hydrocarbon.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ventilate area. Remove ignition sources. No open flames, no sparks, and no smoking. Wear suitable protective clothing. Avoid contact with eyes, skin and clothing.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
- Methods for cleaning up : Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Absorb and/or contain spill with inert material, then place in suitable container. Notify authorities if product enters sewers or public waters.
- Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure adequate ventilation. Use only outdoors or in a well-ventilated area. Use explosion-proof equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use only non-sparking tools. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Avoid breathing mist, spray, vapors. Flammable vapors may accumulate in the container.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.
- Storage conditions : Protect cylinders from physical damage; do not drag, roll, slide or drop. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. No special storage required.
- Incompatible materials : Strong oxidizers. Direct sunlight. Sources of ignition. None known.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Xylene (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
ACGIH OEL TWA	20 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Xylenes (technical or commercial grade)
BEI (BLV)	0.3 g/g Kreatinin Parameter: Methylhippuric acids (The determinants refer to the total of all isomers of methylhippuric acids) - Medium: urine - Sampling time: End of shift

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Xylene (1330-20-7)

Remark	Commercial or technical grade xylenes consist of mixtures of isomers and significant amounts of ethyl benzene as indicated under "Properties." Because ethyl benzene is known to reduce the metabolism of xylenes to methylhippuric acids, the BEI applies to technical or commercial grades of xylenes only. The determinants refer to the total of all isomers of methylhippuric acids
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL (TWA)	435 mg/m ³
	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Mineral Oil (Proprietary)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	5 mg/m ³ inhalable
---------------	-------------------------------

USA - OSHA - Occupational Exposure Limits

OSHA PEL (TWA)	5 mg/m ³
----------------	---------------------

Barium Alkyl-naphthalenesulfonate Mixture (Proprietary)

USA - ACGIH - Occupational Exposure Limits

Local name	As Barium Compounds
ACGIH OEL TWA	0.5 mg/m ³

USA - OSHA - Occupational Exposure Limits

OSHA PEL (TWA)	0.5 mg/m ³
----------------	-----------------------

heptane, n-heptane (142-82-5)

USA - ACGIH - Occupational Exposure Limits

Local name	Heptane, isomers (n-Heptane)
ACGIH OEL TWA	400 ppm
ACGIH OEL STEL	500 ppm
Remark (ACGIH)	TLV® Basis: CNS impair; URT irr
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Heptane (n-Heptane)
OSHA PEL (TWA)	2000 mg/m ³
	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Provide adequate general and local exhaust ventilation.
Environmental exposure controls	: Avoid release to the environment.

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves

Eye protection:

Use suitable eye protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Thermal hazard protection:

Not applicable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Opaque. Green. Liquid.
Color	: Green
Odor	: Solvent
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 35 °C
Flash point	: ≈ -9 °C Based on data available for ingredients
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.713
Solubility	: Practically insoluble in : water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: < 20.5 mm²/s
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: Not oxidising.
Particle Characteristics	: Not applicable

9.2. Other information

VOC content : 82.3%

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Highly flammable liquid and vapor.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Keep away from oxidizers, strong acids and strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Xylene (1330-20-7)

LD50 oral rat	3523 mg/kg Source: ECHA
LD50 dermal rabbit	12126 mg/kg body weight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat	27.124 mg/l/4h

Barium Alkyl-naphthalenesulfonate Mixture (Proprietary)

LD50 oral	Acute toxicity (oral) Not classified
LD50 dermal	Acute toxicity (dermal) Not classified

heptane, n-heptane (142-82-5)

LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 29300 mg/m³

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified. This product does not contain any component that is considered a carcinogen by IARC, ACGIH, OSHA or NTP.

Xylene (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

Xylene (1330-20-7)

STOT-single exposure May cause respiratory irritation.

Heptane, branched, cyclic and linear (426260-76-6)

STOT-single exposure May cause drowsiness or dizziness.

heptane, n-heptane (142-82-5)

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Xylene (1330-20-7)

LOAEL (oral, rat, 90 days) 150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

heptane, n-heptane (142-82-5)

LOAEC (inhalation, rat, vapor, 90 days) 16.6 mg/l air Animal: rat, Animal sex: male

NOAEC (inhalation, rat, vapor, 90 days) 3.3 mg/l air Animal: rat, Animal sex: male

Aspiration hazard : May be fatal if swallowed and enters airways.

Viscosity, kinematic : < 20.5 mm²/s

heptane, n-heptane (142-82-5)

Viscosity, kinematic 0.641 mm²/s at 20 C

Symptoms/effects : Aspiration hazard. May be fatal if swallowed and enters airways. Causes skin irritation. May cause minor eye irritation. May cause drowsiness or dizziness.

Inhalation : High concentration of vapors may induce: headache, nausea, dizziness. May cause minor irritation to the respiratory tract and to other mucous membranes. Intentional abuse may be harmful or fatal.

Skin : May cause slight irritation to the skin. Causes skin irritation.

Eyes : May cause minor eye irritation.

Ingestion : Aspiration hazard. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : No chronic health hazards are likely for this material.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.

Xylene (1330-20-7)

LC50 - Fish [1] 2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)

EC50 - Crustacea [1] > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia

LOEC (chronic) 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

NOEC chronic fish > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

heptane, n-heptane (142-82-5)

EC50 - Crustacea [1]	3.9 mg/l
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

MG-50-5 MOLD GUARD GREEN

Persistence and degradability	No additional information available.
-------------------------------	--------------------------------------

Xylene (1330-20-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Heptane, branched, cyclic and linear (426260-76-6)

Persistence and degradability	Inherently biodegradable.
-------------------------------	---------------------------

Mineral Oil (Proprietary)

Persistence and degradability	No additional information available.
-------------------------------	--------------------------------------

Barium Alkyl-naphthalenesulfonate Mixture (Proprietary)

Persistence and degradability	No additional information available.
-------------------------------	--------------------------------------

heptane, n-heptane (142-82-5)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

Xylene (1330-20-7)

Partition coefficient n-octanol/water (Log Pow)	3.15 Source: HSDB
---	-------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Dispose of in accordance with applicable federal, state, and local regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
1206	1206	1206

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

DOT	IMDG	IATA
14.2. Proper Shipping Name		
Heptanes	HEPTANES	Heptanes
14.3. Transport hazard class(es)		
3	3	3
	 	
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: Yes	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

DOT

UN-No.(DOT)	: UN1206
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

IMDG

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP2

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Colourless, volatile liquids. Explosive limits: 1.1% to 6.7%. n-HEPTANE: flashpoint -4°C c.c. Immiscible with water. Irritating to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
ERG code (IATA)	: 3H

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

MG-50-5 MOLD GUARD GREEN

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Barium AlkylNaphthalenesulfonate Mixture	CAS-No. Proprietary	5 – 10%
--	---------------------	---------

Xylene (1330-20-7)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
-----------	--------

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Xylene(1330-20-7)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List
heptane, n-heptane(142-82-5)	U.S. - New Jersey - Right to Know Hazardous Substance List

MOLD GUARD GREEN

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Revision date : 7/19/2024

Full text of H-phrases	
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Indication of changes:

revised edition. All chapters have been modified since the previous version.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.